



Approvals



15A-300V



Electrical

Rated voltage 450V
 Rated current 20A
 Contact resistance 20mΩ
 Insulation resistance 500MΩ/DC500V
 Withstanding voltage AC2000V/1min
 Wire range 22-12 AWG 2,5mm²

Torque 0,5Nm (4.5Lb in)
 Temp. Range -40°C +105°C
 Stripping length 7 mm
 Max sold. time

Dimensions

Pitch 7,50 mm
 Poles 2÷22

Material

Housing PA66 UL94V0
 Pin
 Cage Copper Alloy, Ni plated
 Screws M3 steel, Zn plated
 Side Block
 Nut screw
 Clamp Phosphore bronze, Ni plated

General description of ordering code

| Series | n. Poles | Pitch | Version | Color | Custom |
|--------|----------|-------|---------|-------|--------|
| CRF | 02÷22 | -7.5 | -F | | |

Version Date

01/21 25/11/2021



euro-block



| linear dimension (Tolerances Standard GB/T 14486-2008) | | | | | | | | | | UNITS: mm | | | |
|--|-------|--------------|---------------|---------------|----------------|-----------------|-------------|-------|----------------|-------------|--------------------|--|--|
| variable range | to 6 | over 6 to 10 | over 10 to 30 | over 30 to 60 | over 60 to 100 | over 100 to 160 | over 160 to | to 10 | over 10 to 100 | over 100 to | SCALE: 10:1 | | |
| tolerance | ±0.20 | ±0.30 | ±0.50 | ±0.70 | ±1.00 | ±1.30 | ±1.60 | 0.10 | 0.30 | 0.60 | SHEET SIZE: ISO A4 | | |



First angle projection

CRF-7.5-F