



### Approvals



8A-250V

### Electrical

Rated voltage	250V
Rated current	8A
Contact resistance	20mΩ
Insulation resistance	500MΩ/DC500V
Withstanding voltage	AC2000V/1min
Wire range	28-16 AWG 1mm <sup>2</sup>
Torque	0,4Nm (3.6Lb in)
Temp. Range	-40°C +105°C
Stripping length	7 mm
Max sold. time	

### Dimensions

Pitch	3,81
Poles	2÷24

### Material

Housing	PA66 UL94V0
Pin	Copper Alloy,Sn plated
Cage	Stainless steel
Screws	
Side Block	
Nut screw	M2.5 steel, Zn plated
Clamp	Phosphour Bronze, Ni plated

### General description of ordering code

Series	n. Poles	Pitch	Version	Color	Custom
CFS	02÷24	-3.81	-F		

### Version Date

19/01 18/10/19



euro-block



linear dimension (Tolerances Standard GB/T 14486-2008)

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

UNITS: mm

SCALE: 10:1

SHEET SIZE: ISO A4



First angle projection

**CFS-3.81-F**