

**Approvals**



8A-250V

**Electrical**

Rated voltage 250V  
 Rated current 8A  
 Contact resistance 20mΩ  
 Insulation resistance 500MΩ/DC500V  
 Withstanding voltage AC2000V/1min  
 Wire range 28-16 AWG 1mm<sup>2</sup>

Torque 0,4Nm (3.6Lb in)  
 Temp. Range -40°C +105°C  
 Stripping length 7 mm  
 Max sold. time

**Dimensions**

Pitch 3,81 mm  
 Poles 2÷24

**Material**

Housing PA66 UL94V0  
 Pin Copper Alloy,Sn plated  
 Cage Stainless steel  
 Screws  
 Side Block  
 Nut screw  
 Clamp Phosphour Bronze, Ni plated

**General description of ordering code**

Series	n. Poles	Pitch	Version	Color	Custom
CFS	02÷24	-3.81			

Version Date


01/22 31/01/2022



**euro-block**



linear dimension (Tolerances Standard GB/T 14486-2008)								UNITS: mm			
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to	SCALE: 10:1
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60	SHEET SIZE: ISO A4



First angle projection

**CFS-3.81**