



### Approvals



8A-300V  
not approved

### Electrical

Rated voltage 250V  
Rated current 7A  
Contact resistance 20mΩ  
Insulation resistance 500MΩ/DC500V  
Withstanding voltage AC1600V/1min  
Wire range 28-16 AWG 1,5mm<sup>2</sup>

Torque 0,2Nm (1.8Lb in)  
Temp. Range -40°C +105°C  
Stripping length 7 mm  
Max sold. time

### Dimensions

Pitch 3,50 mm  
Poles 2÷24

### Material

Housing PA66 UL94V0  
Pin  
Cage Copper Alloy, Ni plated  
Screws M2 steel, Zn plated  
Side Block  
Nut screw  
Clamp Copper Alloy, Ni plated

### General description of ordering code

Series	n. Poles	Pitch	Version	Color	Custom
CRV	02÷24	-3.5	-RF		

### Version Date

21/01 01/03/2021



euro-block



linear dimension (Tolerances Standard GB/T 14486-2008)

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

UNITS: mm

SCALE: 10:1

SHEET SIZE: ISO A4



First angle projection

**CRV-3.5-RF**