



**Approvals**



15A - 300V  
not approved

**Electrical**

Rated voltage 450V  
 Rated current 20A  
 Contact resistance 20mΩ  
 Insulation resistance 500MΩ/DC500V  
 Withstanding voltage AC1600V/1min  
 Wire range 28-12 AWG 2,5mm<sup>2</sup>

Torque  
 Temp. Range -40°C +105°C  
 Stripping length 7 mm  
 Max sold. time

**Dimensions**

Pitch 5,08 mm  
 Poles 2÷24

**Material**

Housing PA66 UL94V0  
 Pin  
 Cage Copper Alloy, Ni plated  
 Screws  
 Side Block  
 Nut screw  
 Clamp

General description of ordering code

Series	n. Poles	Pitch	Version	Color	Custom
CFF	02÷24	-5.08	-F		

Version Date

01/21 08/10/2021



**euro-block**



linear dimension (Tolerances Standard GB/T 14486-2008)

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



UNITS: mm

SCALE: 10:1

SHEET SIZE: ISO A4



First angle projection

**CFF-5.08-F**